

Date de la dernière modification
09/11/2023

HL-103

Rotating gate valve lockout from 165 to 254 mm diameter

Series: HL-10.



<p>Application :</p> <ul style="list-style-type: none"> To prevent operation of a rotating gate valve once installed. <p>Characteristics :</p> <ul style="list-style-type: none"> Condemner for handwheel valves, good resistance to cracking, operating temperature 90 °C max. Red polyurethane material. Size 350 x 270 x 60 mm, 3 padlock locking, hole Ø 9 mm, valve Ø 165 to 254 mm. "DANGER" marking, "DO NOT TOUCH" pictogram. 	<p>Description</p> <p>Use</p> <p>Color</p> <p>Composition</p> <p>Use</p> <p>Number Of Padlocks</p> <p>Number Holes</p> <p>Hole</p> <p>Inner</p> <p>Dimensions</p> <p>Capacity</p> <p>Dimensions</p> <p>Height</p> <p>Width</p> <p>Depth</p> <p>Fonctionnalité</p> <p>Weight</p> <p>Material</p> <p>Longueur</p> <p>Length</p>	<p>Indoor & Outdoor</p> <p>Array</p> <p>2 parties articulées</p> <p>Indoor & Outdoor</p> <p>1</p> <p>1</p> <p>10</p> <p>257</p> <p>Ø volant : 165 à 254 mm</p> <p>Ø 267 x 63</p> <p>63 mm</p> <p>Ø 267</p> <p>0,67</p> <p>Polyuréthane</p>
--	---	--