

Date de la dernière modification
09/11/2023

HL-201

Adjustable quarter turn ball valve lockout,
206 x 78 x 95 mm

Series: HL-20.



<p>Application :</p> <ul style="list-style-type: none"> • For locking quarter-turn type valves. • Completely locks the valve and thus prevents operation. <p>Caracteristics :</p> <ul style="list-style-type: none"> • Adjustable condemner 1/4 turn valves, good resistance to cracking, operating temperature 90 °C maximum. • Red polyurethane material. • Dimensions 280 x 200 x 90 mm, Padlocking by padlock-13 positions, holes Ø 7 mm, valve locking Ø 38,10 to 63,5 mm. • "DANGER" marking, pictogram "DEFENSE TO OPERATE"-1 identification zone involved. 	<p>Description</p> <p>Use</p> <p>Color</p> <p>Use</p> <p>Number Of Padlocks</p> <p>Hole</p> <p>Dimensions</p> <p>Capacity</p> <p>Dimensions</p> <p>Thickness</p> <p>Width</p> <p>Fonctionnalité</p> <p>Weight</p> <p>Material</p> <p>Longueur</p> <p>Length</p>	<p>Indoor & Outdoor</p> <p>Array</p> <p>Indoor & Outdoor</p> <p>1</p> <p>7</p> <p>13 positions de réglage - Serrage sur tuyaux de Ø 21 à 160 mm</p> <p>206 x 95 x 78</p> <p>78</p> <p>95</p> <p>0,18</p> <p>POLYURETHANE</p> <p>206</p>
--	---	---